

Product availability : Stock - Normally stocked in distribution facility



Price* : 270.00 USD



Main

Product or component type	Industrial Control Transformer
Rated power in VA	50 VA
Primary voltage	208/230/460 V
Secondary voltage	115 V
Range of product	TF

Complementary

Phase	1 phase
Rated power in VA	50 VA
Primary voltage	208/230/460 V : 115 V
Fuse type	CC 0.41 x 1.50 in top
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Height	4.81 in
Width	3.38 in
Depth	3.34 in
Material	Copper winding
Product compatibility	FSC1


Environment

Product certifications	CE UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	Not rated (open device)
Insulation temperature	221 °F (105 °C)

Ordering and shipping details

Category	16202 - 9070 TF (NOT T) 50-200VA
Discount Schedule	CP8
GTIN	00785901039273
Nbr. of units in pkg.	1
Package weight(Lbs)	4.3500000000000005
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1227 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------