



Main

Range of product	9080G
Product or component type	Terminal block transient voltage suppressor
Product or component type	Terminal block
Color	Natural
Quantity per set	Set of 5

Complementary

System Voltage	120 V AC
AWG gauge	AWG 18...AWG 10 (copper)
Mounting support	35 mm DIN rail 9080GH track
Product certifications	CE UL recognized E60616 CCN XCFR2 CSA file 62144 class 6228 01
Protection type	Fingersafe per: DIN 57470
Electrical connection	Box lugs copper
Material	Nylon block
Ambient air temperature for operation	-40...257 °F
Connections - terminals	Lug copper Tightening Torque: 18...20 lbf.in for: AWG 18...AWG 10 (copper)
Height	2.55 in
Width	2.16 in
Depth	0.5 in
Number of terminal blocks	24 per foot
Product compatibility	GT6B

Environment

Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0845 - Schneider Electric declaration of conformity	Compliant - since 0845 - Schneider Electric declaration of conformity

Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.