

Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|---------------------------|-------------------------------------|
| Range of product | Square D |
| Product or component type | Energy Efficient Transformer |
| Device application | Low voltage electrical distribution |
| Number of tap-offs | 1-5 % FCAN 2-5 % FCBN |

Complementary

| | |
|-------------------------------|--|
| Primary voltage | 208 V delta |
| Rated operational power in VA | 30 kVA |
| Type of cooling | Natural convection |
| Secondary voltage | 480Y/277 V |
| Network frequency | 60 Hz |
| Phase | 3 phases |
| AWG gauge | AWG 6...350 kcmil |
| Temperature rise | 150 °C 220 °C insulated |
| Material | Aluminium |
| Mounting support | Floor Ceiling, with specific accessories Wall, with specific accessories |
| Depth | 21 in (533.4 mm) |
| Width | 25.5 in (647.7 mm) |
| Height | 897.13 mm |
| Product weight | 179.17 kg |

Environment

| | |
|----------------------|-----------------------|
| Standards | UL 1561 NEMA ST-20 |
| Degree of protection | UL type 1 |

Ordering and shipping details

| | |
|-----------------------|---|
| Category | 16250 - 3PH EX/2016 15-150KVA LVGP XFMR |
| Discount Schedule | PE2X |
| GTIN | 00785901474487 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 435 |
| Returnability | N |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1601 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |