

Product availability : Stock - Normally stocked in distribution facility

Price* : 3377.00 USD



Main

Range	TeSys
Product name	TeSys GS
Device short name	GS2S
Product or component type	Switch-disconnector-fuse
Poles description	3P
Protected poles description	3t
Contacts type and composition	3 NO
[I _{th}] conventional free air thermal current	600 A at 104 °F (40 °C)
[I _e] rated operational current	600 A on AC-22A 600 A on AC-23A
Fuse type	UL
Fuse size	J
Network type	AC DC
Network frequency	50/60 Hz

Complementary

Type of operating handle	External frontal
Mounting support	Plate
[U _{imp}] rated impulse withstand voltage	12 kV
Short-circuit withstand	77 kA
Connections - terminals	Power circuit : lugs-ring terminals 2 cable 150 mm ² Power circuit : bars cable 100 mm ²
Tightening torque	Power circuit: 309.73 lbf.in (35 N.m)

Environment

Standards	CSA C22.2 No 4 UL98
IP degree of protection	IP20 with terminal cover conforming to IEC 60529
Ambient air temperature for operation	-4...158 °F (-20...70 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)
Fire resistance	1760 °F (960 °C) body
Height	11.81 in (300 mm)
Width	14.33 in (364 mm)
Depth	9.84 in (250 mm)
Product weight	63.93 lb(US) (29 kg)

Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901550495
Nbr. of units in pkg.	1
Package weight(Lbs)	45
Returnability	Y
Country of origin	FR

Contractual warranty

Warranty period	18 months
-----------------	-----------