



Main

Disconnecter device type	Fusible disconnect switch
Enclosure type	Enclosure standard environment indoor
Series name	Heavy duty

Complementary

Rated current	60 A
AWG gauge	AWG 14...AWG 3 aluminium/copper
Device composition	Neutral (factory installed)
Device mounting	Surface
Electrical connection	Lugs
Enclosure material	Steel
Number of poles	3
Permissible voltage	<= 240 V AC <= 250 V DC
Short-circuit protection	200 kA R or J 10 kA H or K
Switch function	TPST

Environment

contacts type and composition	1 NO/1 NC
NEMA degree of protection	NEMA 1
product certifications	UL listed

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1313 - Schneider Electric declaration of conformity	Compliant - since 1313 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------