



## Main

|                           |   |
|---------------------------|---|
| Product or component type | Single Throw Safety Switch              |
| Line Rated Current        | 200 A                                   |
| Product certifications    | UL listed                               |
| NEMA degree of protection | NEMA 4X fiberglass reinforced polyester |
| Device composition        | None                                    |
| Disconnecter device type  | Fusible disconnect                      |
| Short-circuit current     | 10 kA H or K<br>200 kA R, J or L        |
| Device mounting           | Surface                                 |
| Number of poles           | 3                                       |
| Electrical connection     | Lugs                                    |
| Series name               | Heavy duty                              |
| System Voltage            | 600 V AC/DC                             |
| AWG gauge                 | AWG 6...250 kcmil (copper or aluminium) |

## Complementary

## Environment

## Offer Sustainability

|  |  |
|--|--|
| Green Premium product  | Green Premium product  |
| Compliant - since 1313 - Schneider Electric declaration of conformity  | Compliant - since 1313 - Schneider Electric declaration of conformity  |
| Reference not containing SVHC above the threshold  | Reference not containing SVHC above the threshold  |
| Available  | Available  |
| Need no specific recycling operations  | Need no specific recycling operations  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:   |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.