HDA260452





Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip unit technology	Thermal-magnetic
Breaking capacity code	D

Complementary

Complementary		
Line Rated Current	45 A	
Poles description	2P	
Breaking capacity	18 kA at 480 V AC 25 kA at 240 V AC 14 kA at 600 V AC 20 kA at 250 V DC	
System Voltage	250 V DC 600 V AC	
Continuous current rating	80 %	_
Mounting mode	I-Line	_
Electrical connection	I-Line connection line Lugs load	
AWG gauge	AWG 14AWG 3/0 (aluminium/copper)	
Phase connection	AC	
Magnetic hold current	400 A	
Magnetic tripping current	850 A	
Height	9.73 in	
Width	2.94 in	
Depth	4.8 in	

Environment

product certifications	CE CSA IEC UL listed
ambient air temperature for operation	104 °F (40 °C)

Offer Sustainability

Green Premium product	Green Premium product	
Compliant - since 0832 - Schneider Electric declaration of conformity	Compliant - since 0832 - Schneider Electric declaration of conformity	
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold	
Available	Available	
Need no specific recycling operations	Need no specific recycling operations	
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:	
DINP, which is known to the State of California to cause cancer, and	DINP, which is known to the State of California to cause cancer, and	

DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.	DIDP, which is known to the State of California to cause Birth Defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov
Contractual warranty	
Warranty period	18 months

