

Product availability : Stock - Normally stocked in distribution facility



Price\* : 4939.00 USD



### Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Electronic standard Micrologic 3.2 S LSI
Breaking capacity code	G

### Complementary

Line Rated Current	250 A
Number of poles	3
Poles description	3P
Breaking capacity	65 kA 240 V AC 35 kA 480 V AC 18 kA 600 V AC
System Voltage	600 V AC
[Ics] rated service short-circuit breaking capacity	100 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
AWG gauge	AWG 3/0...350 kcmil (aluminium/copper)

### Environment

Product certifications	CCC CE CSA IEC UL listed
Ambient air temperature for operation	122 °F (50 °C)

## Ordering and shipping details

Category	01107 - H/J ELEC TRIP UNIT MOUNT BREAKER/SW
Discount Schedule	DE2
GTIN	00785901655237
Nbr. of units in pkg.	1
Package weight(Lbs)	5
Returnability	N
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

## Contractual warranty

Warranty period	18 months
-----------------	-----------