

Product availability : Stock - Normally stocked in distribution facility



Price\* : 8168.00 USD



### Main

Product or component type	Circuit breaker
Range of product	PowerPact M
Current sensor rating range	500 A
Breaking capacity code	G
Trip unit technology	Electronic basic ET 1.0 LI

### Complementary

Line Rated Current	500 A
System Voltage	600 V AC
Mounting mode	I-Line
Poles description	3P
Breaking capacity	65 kA at 240 V AC 35 kA at 480 V AC 18 kA at 600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...500 kcmil (aluminium/copper) for 3 cable(s)
Magnetic tripping current	1000...5000 A

### Environment

Product certifications	CSA IEC UL listed
------------------------	-------------------------

### Ordering and shipping details

Category	01200 - MG, MJ I-LINE BREAKER
----------	-------------------------------

Discount Schedule	DE2
GTIN	00785901467908
Nbr. of units in pkg.	1
Package weight(Lbs)	28.93
Returnability	Y
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

### Contractual warranty

Warranty period	18 months
-----------------	-----------