

Product availability : Stock - Normally stocked in distribution facility



Price* : 5960.00 USD



Main

| | |
|-----------------------------|----------------------------|
| Product or component type | Circuit breaker |
| Range of product | PowerPact M |
| Current sensor rating range | 400 A |
| Breaking capacity code | G |
| Trip unit technology | Electronic basic ET 1.0 LI |

Complementary

| | |
|---|---|
| Line Rated Current | 400 A |
| System Voltage | 600 V AC |
| Mounting mode | Unit mount |
| Poles description | 2P |
| Breaking capacity | 65 kA at 240 V AC 35 kA at 480 V AC 18 kA at 600 V AC |
| [Ics] rated service short-circuit breaking capacity | 80 % |
| Electrical connection | Lugs load Lugs line |
| AWG gauge | AWG 3/0...500 kcmil (aluminium/copper) for 3 cable(s) |

Environment

| | |
|------------------------|-------------------------|
| Product certifications | CSA IEC UL listed |
|------------------------|-------------------------|

Ordering and shipping details

| | |
|-------------------|-----------------------------------|
| Category | 01205 - MG, MJ UNIT MOUNT BREAKER |
| Discount Schedule | DE2 |

| | |
|-----------------------|----------------|
| GTIN | 00785901507567 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 28 |
| Returnability | Y |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Available |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|