

Product availability : Stock - Normally stocked in distribution facility



Price* : 9929.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact M
Current sensor rating range	300 A
Breaking capacity code	J
Trip unit technology	Electronic basic ET 1.0 LI

Complementary

Line Rated Current	300 A
System Voltage	600 V AC
Mounting mode	Plug-in
Poles description	3P
Breaking capacity	65 kA at 480 V AC 25 kA at 600 V AC 100 kA at 240 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...500 kcmil (aluminium/copper) for 3 cable(s)
Magnetic tripping current	600...3000 A

Environment

Product certifications	CSA IEC UL listed
------------------------	-------------------------

Ordering and shipping details

Category	01200 - MG, MJ I-LINE BREAKER
----------	-------------------------------

Discount Schedule	DE2
GTIN	00785901689560
Nbr. of units in pkg.	1
Package weight(Lbs)	28.740000000000002
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------