




Price* : 1.80 USD



Main

Range	Linery
Product name	Linery TR
Product or component type	Terminal block
Device short name	TRR
Accessory / separate part category	Connection accessory
Terminal block type	Passthrough
Terminal block level	1
Mounting mode	Clip-on
Nominal cross section	0 in ² (2.5 mm ²)
Length	2.38 in (60.5 mm)
Colour	Blue
Quantity per set	Set of 50

Complementary

Width	0.2 in (5.2 mm)
Height	1.44 in (36.5 mm)
Connections - terminals	1 x spring terminal : upstream 2 x spring terminal : downstream
Number of terminals	3
Connection position	Top
Number of measurement input	2
Cable cross section	0.08...2.5 mm ² , flexible without cable end 0.08...4 mm ² , solid with cable end 0.2...2.5 mm ² , flexible with cable end 0.08...4 mm ² , solid without cable end
Wire stripping length	0.39 in (10 mm)
Tool type	Connection : flat screwdriver

Disconnection : flat screwdriver

System Voltage	600 V CSA 600 V cURus 800 V conforming to EN/IEC 60947-7-1
[Ie] rated operational current	20 A CSA 20 A cURus 24 A conforming to EN/IEC 60947-7-1
Material	Polyamide 6/6 (insulating case) Copper alloy (connector and screw) Copper alloy (commoning link) Chromium-nickel steel (spring)
Dielectric loss	0.01 at 1 MHz conforming to IEC 60250 0.01 at 1 MHz conforming to VDE 0303-T4
Dielectric constant	3.7 at 1 MHz
Resistivity	10000 MΩ.m conforming to IEC 60093 10000 MΩ.m conforming to VDE 0303-T30
Surface resistance	1000 GΩ conforming to IEC 60093 1000 GΩ conforming to VDE 0303-T30
Creep resistance	500 CTI (> 400 kB) conforming to IEC 60093 500 CTI (> 400 kB) conforming to VDE 0303-T30
Flame retardance	V0, thickness 0.03 in (0.8 mm) conforming to UL 94
Product weight	0.25 oz (7 g)
Range compatibility	Prisma - G Prisma - P Pragma Prisma - PH Prisma - Pack Spacial Kaedra TeSys
Product compatibility	Spacial enclosures


Environment

Product certifications	ATEX CSA cURus DNV GL LR VDE IEC-Ex EAC
Dielectric strength	1000 V conforming to IEC 60243-1
Ambient air temperature for operation	-40...266 °F (-40...130 °C) conforming to IEC 60216-1 -40...266 °F (-40...130 °C) conforming to VDE 0304-T21

Ordering and shipping details

Category	21715 - IEC TERMINAL BLOCKS-NSY,AM1,DF6,GK1
Discount Schedule	CP5
GTIN	00785901724667
Nbr. of units in pkg.	50
Package weight(Lbs)	0.02
Returnability	Y
Country of origin	DE

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1052 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold

Reference not containing SVHC above the threshold

Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------
