

Product availability : Stock - Normally stocked in distribution facility



Price* : 28058.00 USD



Main

Product or component type	Circuit breaker
Range of product	PowerPact P
Current sensor rating range	800 A
Breaking capacity code	J
Trip unit technology	Electronic ammeter Micrologic 6.0 A LSIG
Device short name	A

Complementary

Line Rated Current	800 A
Product certifications	CSA IEC UL listed
System Voltage	600 V AC
Mounting mode	I-Line
Poles description	3P
Breaking capacity	65 kA at 480 V AC 25 kA at 600 V AC 100 kA at 240 V AC
[Ics] rated service short-circuit breaking capacity	100 %
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...500 kcmil (aluminium/copper) 3
Height	14.85 in
Depth	8.07 in
Width	8.96 in

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	01210 - PG,H,J,K,L,N I-LINE BREAKERS
Discount Schedule	DE2
GTIN	00785901497141
Nbr. of units in pkg.	1
Package weight(Lbs)	38
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------