

Product data sheet

Characteristics

QDP22225TM

PowerPact Q - molded case circuit breaker - 2-pole - 25 kA - 240 V - 225 A

Product availability : Stock - Normally stocked in distribution facility



Main

Product or component type	Circuit breaker
Range of product	PowerPact Q
Trip unit technology	Thermal-magnetic
Provided equipment	Lug at OFF end Stud with nut and washer at ON end

Complementary

Line Rated Current	225 A
System Voltage	240 V AC
Number of poles	2
Breaking capacity	25 kA 240 V AC
[Ics] rated service short-circuit breaking capacity	50 %
Breaking capacity code	D
Mounting mode	Unit mount
Electrical connection	Lugs on load: AWG 4...300 kcmil (aluminium/copper) Terminal nut on line
Magnetic hold current	1200 A
Magnetic tripping current	2400 A

Environment

Product certifications	CSA IEC UL listed
------------------------	-------------------------

Ordering and shipping details

Category	00024 - Q2 & QE METERING BREAKERS
----------	-----------------------------------

Discount Schedule	DE2A
GTIN	00785901568957
Nbr. of units in pkg.	1
Package weight(Lbs)	3.2600000000000002
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 4Q2016 Will be compliant on 4Q2016

Contractual warranty

Warranty period	18 months
-----------------	-----------