Product data sheet Characteristics

QO220PL5392

QO Miniature Circuit Breaker 20A 2P 120/240V 10kA Plug-in Mount

Product availability: Stock - Normally stocked in distribution facility





Main

Product or component type	Circuit breaker	9
Range of product	QO	5
Line Rated Current	20 A	
System Voltage	120/240 V AC	
Mounting mode	Plug-in	<u> </u>
Poles description	2P	
Circuit breaker type	Standard	ide Silve
Circuit breaker application	HACR rated	
Electrical connection	Box lugs	

Complementary

Breaking capacity	10 kA at: 120/240 V AC	9
Number of spaces required	2	+
Provided equipment	48 in lead	. v.
AWG gauge	AWG 12AWG 2 (aluminium) AWG 14AWG 2 (copper)	te for
Height	4.55 in	
Depth	2.91 in	
Width	1.5 in	אינים ס ס

Environment

Product certifications	UL listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00912 - POWERLINK BREAKERS
Discount Schedule	DE8A
GTIN	00785901084143
Nbr. of units in pkg.	1
Package weight(Lbs)	0.910000000000003
Returnability	Υ
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
	·