

Product availability : Stock - Normally stocked in distribution facility



### Main

Product or component type	Load Center
Range of product	QO
Load center type	Main lugs
Line Rated Current	70 A
Number of spaces	2
Short-circuit current	65 kA
Number of circuits	4
Number of tandem circuit breakers	2
Phase	1 phase
System Voltage	120/240 V AC

### Complementary

AWG gauge	AWG 12...AWG 3 (aluminium) AWG 14...AWG 4 (copper)
NEMA degree of protection	NEMA 1 indoor
Cover type	Surface cover
Electrical connection	Lugs
Device composition	Grounding bar (ordered separately)
Electrical connection	Lugs
Wiring configuration	3-wire
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel grey
Box number	2
Product certifications	UL listed
Height	9.29 in (236 mm)
Width	4.8 in (122 mm)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Ordering and shipping details

Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	00785901785149
Nbr. of units in pkg.	1
Package weight(Lbs)	3.8100000000000001
Returnability	Y
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1423 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------