



Main

| | |
|---------------------------|-------------------------|
| Product or component type | Surge protection device |
| Range of product | QO |

Complementary

| | |
|---|---------------------------|
| Surge current | 50 kA |
| System Voltage | 120/240 V AC |
| Phase | 1 phase |
| Wiring configuration | 3-wire |
| Connections - terminals | Plug in phase and neutral |
| [Uc] maximum continuous operating voltage | 150 V |
| Nominal discharge current | 20 kA |
| Short-circuit protection | 22 kA |
| Height | 3.98 in (101 mm) |
| Width | 1.5 in (38 mm) |
| Depth | 2.6 in (66 mm) |

Environment

| | |
|---------------------------------------|-------------------------------------|
| NEMA degree of protection | NEMA 2 |
| enclosure material | Plastic, colour : black |
| standards | UL 1449 ed. 4 CSA C22.2 No 269.1 |
| ambient air temperature for operation | 149 °F (65 °C) |

Offer Sustainability

| | |
|---|---|
| Green Premium product | Green Premium product |
| Compliant - since 1651 - Schneider Electric declaration of conformity | Compliant - since 1651 - Schneider Electric declaration of conformity |
| Reference not containing SVHC above the threshold | Reference not containing SVHC above the threshold |
| Available | Available |
| Available | Available |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.