# Product data sheet Characteristics

# QON2L40 OEM MOUNTING BASE 2SP 40A

Product availability: Stock - Normally stocked in distribution facility



## Main

D ( 1 1	^^	
Range of product	( )( )	
range of product	QO	

# Complementary

Main		
Range of product	QO	
- tango or product		
Complementary		
[In] rated current	40 A	
System Voltage	120/240 V AC	
AWG gauge	AWG 12AWG 6 aluminium cable AWG 14AWG 6 copper cable	
Material	Tin plated aluminium busbar	
Network number of phases	1 phase	
Number of spaces	2	
Short-circuit protection	10 kA	
Product compatibility	QO circuit-breaker	
Product destination	QO circuit breaker QO-GFI circuit breaker QO-EPD circuit breaker	
Wiring configuration	2-wire	
Environment		
Product certifications	CSA UL	
Ordering and chinning details		
Ordering and shipping details Category	00909 - MOUNTING BASES, S/N	
Discount Schedule	DE3A	
GTIN	00785901804581	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.2800000000000000	
Returnability	Υ	
Neturnability	<u> </u>	

## Environment

Product certifications	CSA
	UL

## Ordering and shipping details

Category	00909 - MOUNTING BASES, S/N	
Discount Schedule	DE3A	
GTIN	00785901804581	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.2800000000000003	
Returnability	Υ	

Country of origin	MX
Contractual warranty	
Warranty period	18 months