Product data sheet Characteristics

QOU3000

QOU Non-Automatic Miniature Switch, 100A, 3P, 240V, 10kA

Product availability: Stock - Normally stocked in distribution facility







Main

		ų.
Product or component type	Switch	• • • • • • • • • • • • • • • • • • •
Range of product	QOU	
Circuit breaker application	HACR and Switching Duty rated	-

Complementary

		-
Line Rated Current	100 A	ئ <u>ڍ</u>
Poles description	3P	: :- :-
Breaking capacity	5 kA at: 48 V DC 10 kA at: 240 V AC	ninira
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side	for deter
System Voltage	240 V AC 48 V DC	ed ex
Mounting mode	Unit mount	
AWG gauge	AWG 12AWG 2/0 (aluminium/copper)	<u>.</u> 7.
Height	4.45 in	
Depth	2.95 in	
Width	2.25 in	, , , , , , , , , , , , , , , , , , ,

Environment

D. J. J. 1977 19	
Product certifications CSA UL listed	

Ordering and shipping details

Category	00900 - QOU BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	00785901060345

Nbr. of units in pkg.	1
Package weight(Lbs)	1.350000000000001
Returnability	Υ
Country of origin	MX

Offer Sustainability

Green Premium product
Compliant - since 1323 - Schneider Electric declaration of conformity
Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold
Reference not containing SVHC above the threshold
Available
Need no specific recycling operations

Contractual warranty

o in a data in a large		
Warranty period	18 months	