Product data sheet Characteristics

QUM400CL METER MAIN UG 400A LEVER BYPASS DGM

Product availability: Stock - Normally stocked in distribution facility





Main

Product or component type	Meter Mains
Range of product	QO

Complementary

Complementary		.
Line Rated Current	400 A	<u></u>
Short-circuit current	65 kA	
Meter socket type	Ringless	
Device mounting	Surface Semi flush field installed flange kit	: <u>:</u> :: :: :: ::
Number of spaces	0	
Number of circuits	0	-
Product mounting	Surface Semi-flush with field installed flange kit	, , , , , , , , , , , , , , , , , , ,
Number of tandem circuit breakers	0	9
Hub type	A-L	<u>\$</u>
Electrical connection	Lugs service ground Studs line side	<u></u>
AWG gauge	AWG 4250 kcmil (aluminium) service ground AWG 4250 kcmil (copper) service ground	
Device composition	Service disconnect (factory installed)	
Service disconnect rated current	400 A	
Service feed location	UG	
Bypass type	Class 320 lever bypass	

Ordering and shipping details

O P O		
Category	00148 - HOMELINE CSED DEVICES	gocni
Discount Schedule	DE3A	This
GTIN	00785901611509	mer:
Nbr. of units in pkg.	1	is clai

Package weight(Lbs)	120	
Returnability	N	
Country of origin	MX	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 4Q2016
	Will be compliant on 4Q2016

Contractual warranty

Warranty period	18 months