Product data sheet Characteristics

RC2040M150CH ALL-IN-ONE RINGLESS HORN OH/UG 150A

Product availability: Stock - Normally stocked in distribution facility





Main

		S contract to the second contract to the seco
Product or component type	All-In-One	
Range of product	Homeline	
Meter socket type	Ringless	
Hub type	A	9

Complementary

<u> </u>		
Line Rated Current	150 A	
Short-circuit current	22 kA	
Device mounting	Surface	
Number of spaces	20	
Product mounting	Surface	
Number of circuits	40	
Number of tandem circuit breakers	20	
Electrical connection	Lugs line side Lugs service ground	
AWG gauge	AWG 6350 kcmil (aluminium) line side AWG 6350 kcmil (copper) line side AWG 12AWG 2/0 (aluminium) service ground AWG 12AWG 2/0 (copper) service ground	
Device composition	Service disconnect (factory installed)	
Service disconnect rated current	150 A	
Branch circuit breaker rated current	150 A	
Service feed location	OH UG	
Bypass type	Horn bypass	

Ordering and shipping details

Category	00048 - HOM METER MAINS	ner:
Discount Schedule	DE3A	olain

GTIN	00785901878315
Nbr. of units in pkg.	1
Package weight(Lbs)	42.75
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0944 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Warranty period	18 months
-----------------	-----------