
Product data sheet Characteristics

RL05512 REACTOR DRIVE LINE 3PH 20HP 208/230V T-1

Product availability: Stock - Normally stocked in distribution facility



Complementary

Complementary		
[In] rated current	55 A	
AWG gauge	AWG 6AWG 1/0	
Depth	13.09 in	
Electrical connection	Screw clamp terminal	
Height	13 in	
Permissible voltage	<= 600 V AC	
Product weight	45 lb(US)	
Protection type	Harmonic distortion Current protection	
	Overvoltage protection	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	13.22 in	
Width Environment	10.22 III	
Environment	CE CSA LR29753 UL listed file E180243	
Environment Product certifications	CE CSA LR29753 UL listed file E180243	
Environment Product certifications Ordering and shipping de	CE CSA LR29753 UL listed file E180243	
Environment Product certifications Ordering and shipping de Category	CE CSA LR29753 UL listed file E180243	
Environment Product certifications Ordering and shipping de Category Discount Schedule	CE CSA LR29753 UL listed file E180243 stails 22062 - LINE REACTORS/FILTERS (RL,KLC)	
Environment Product certifications Ordering and shipping de Category Discount Schedule GTIN	CE CSA LR29753 UL listed file E180243 Stails 22062 - LINE REACTORS/FILTERS (RL,KLC) CP4C	
Environment Product certifications Ordering and shipping de Category Discount Schedule GTIN	CE	
Environment Product certifications Ordering and shipping de Category Discount Schedule GTIN Nbr. of units in pkg.	CE	
Environment Product certifications Ordering and shipping de Category Discount Schedule GTIN Nbr. of units in pkg. Package weight(Lbs)	CE	
Environment Product certifications Ordering and shipping de Category Discount Schedule GTIN Nbr. of units in pkg. Package weight(Lbs) Returnability	CE	

Environment

Product certifications	CE CSA LR29753
	UL listed file E180243

Ordering and shipping details

or dorning direct or ripping dottains				
Category	22062 - LINE REACTORS/FILTERS (RL,KLC)	.; .; .;		
Discount Schedule	CP4C			
GTIN	00785901143789			
Nbr. of units in pkg.	1	<u> </u>		
Package weight(Lbs)	45			
Returnability	N			
Country of origin	US			

Contractual warranty

Warranty period	1	3 months	