Product data sheet Characteristics

XZCB11001H

AS-Interface - flat connecting cable - TPE - yellow - 100 m

Product availability: Stock - Normally stocked in distribution facility



Main

TTIGHT	
Accessory / separate part category	Connection accessories
Accessory / separate part type	Connecting cable
Accessory / separate part designation	AS-Interface flat cable
Accessory / separate part destination	AS-Interface cabling system
Cable length	328.08 ft (100 m)
Wire insulation material	TPE
Color	Yellow

Complementary

Clamping connection capacity	2 x 1.5 mm²
[Ue] rated operational voltage	<= 48 V
Product weight	15.43 lb(US) (7 kg)

Environment

IP degree of protection	IP67	_ ;
Ambient air temperature for operation	-22221 °F (-30105 °C)	_
Ambient air temperature for storage	-40221 °F (-40105 °C)	-
Environmental characteristic	Oil and vapour resistant	

Ordering and shipping details

THE PROPERTY AND STORY AND STORY		
		,
		,
Main		
Accessory / separate part category	Connection accessories	
Accessory / separate part type	Connecting cable	
Accessory / separate part designation	AS-Interface flat cable	
Accessory / separate part destination	AS-Interface cabling system	
Cable length	328.08 ft (100 m)	
Wire insulation material	TPE	
Color	Yellow	
Complementary		
Clamping connection capacity	2 x 1.5 mm²	
[Ue] rated operational voltage	<= 48 V	
Product weight	15.43 lb(US) (7 kg)	
	, , , , ,	
E. to const		
Environment	ID07	
IP degree of protection	IP67	
Ambient air temperature for operation	-22221 °F (-30105 °C)	
Ambient air temperature for storage	-40221 °F (-40105 °C)	
Environmental characteristic	Oil and vapour resistant	
Ordering and shipping details		•
Category	18325 - SERIPLEX SOFTWARE&CABLES DISC SPX2	
Discount Schedule	SPX2	
GTIN	00785901180913	
Nbr. of units in pkg.	1	
Package weight(Lbs)	15	
Returnability	N	
Con 20, 2017		

Country of origin	AT	
Offer Sustainability		
Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Will be compliant on 3Q2013	
	Will be compliant on 3Q2013	
Contractual warranty		
Warranty period	18 months	