3000 Series Midsized Commercial Fan Forced Wall Heater - Multiple Wattage

Features

- Wattage selectable at time of installation.
- Models shipped wired to highest wattage.
- Approved for horizontal mounting - right or left discharge.
- Fan purge circuit.
- Disconnect switch.
- Drywall depth embossments on back can.
- 18 gauge powder coated steel & extruded Aluminum front.
- Manual reset thermal limit.
- Steel block fin element.
- Propeller style fan blade: 1060 RPM motor; 100 CFM.
- Weight 6 lbs.
- Rough in dimensions: 9 ¼” Wide x 12 ⅛” High x 3 ⅝” Deep.
- Grill dimensions: 10” Wide x 13 ⅛” High.
- Approved for wall or ceiling installation.
- Made in U.S.A.

Standard Models

MFG CATALOG NUMBER	MFG MODEL NUMBER	SELECTABLE INSTALLATION WATTAGE	MAX BTUs	VOLTS	MAX AMPS
TAMPERPROOF IN-BUILT DOUBLE POLE THERMOSTAT (40º - 100º TEMPERATURE RANGE)					
09962102	E3055T2DWB	750 or 1500	5120	120	12.5
09962202	E3058T2DWB	900 or 1800	6143	120	15.0
09962502	F3052T2DWB	1000 or 2000	6826	208	8.3
09456902	F30522T2DWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	208	10.8
09962802	H3052T2DWB	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3
09457202	H30522T2DWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	240	9.4
09963102	G3052T2DWB	2000	6826	277	7.2
TAMPERPROOF IN-BUILT SINGLE POLE THERMOSTAT (0º - 110º TEMPERATURE RANGE)					
09960602	E3055TDWB	750 or 1500	5120	120	12.5
09960702	E3058TDWB	900 or 1800	6143	120	15.0
09961002	F3052TDWB	1000 or 2000	6826	208	8.3
09456302	F30522TDWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	208	10.8
09961302	H3052TDWB	750 or 1000 - 1500 or 2000	6826	208 / 240	8.3
09456602	H30522TDWB	500 or 750 or 1000 or 1250 or 1500 or 1750 or 2250	7680	240	9.4
09961602	G3052TDWB	2000	6826	277	7.2

Accessories

MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION
09969402	305EX8	1” EXTENDER
09969302	305EX16	2” EXTENDER
09969202	305EX32	4” SURFACE MOUNT FRAME