

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Protect It! 6-Outlet Surge Protector, 6 ft. (1.83 m) Cord, 790 Joules, Diagnostic LED, Black Housing

MODEL NUMBER: TLP606B









Safeguard your computer, printer, scanner, router, modem and other small home electronics against dangerous surges, spikes and line noise. Recommended for any desktop, network or home application requiring AC line protection.

Description

Perfect for your home or office workstation, the TLP606B Protect It!® 6-Outlet Surge Protector features a surge protection rating of 790 joules to defend your sensitive electronic components against strong surges and spikes. In fact, Tripp Lite will repair or replace any connected equipment damaged by surges, including direct lightning strikes, up to \$20,000 for life (valid in the U.S., Canada and Puerto Rico only).

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP606B protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G). It also filters out electromagnetic interference (EMI) and radio frequency interference (RFI) that can disrupt your electronics and inflict hardware damage or data loss.

Your devices plug into six NEMA 5-15R outlets, one of which is placed at the end to accept a bulky transformer without blocking adjacent outlets. An integrated 15A circuit breaker protects all outlets and shuts down connected equipment in case of overload. The lighted on/off switch provides one-touch control over connected equipment. A diagnostic LED confirms your connected equipment is protected.

The 6-ft. (1.83 m) AC power cord with NEMA 5-15P plug reaches nearby outlets to fit easily into your workstation or home theater setup. Keyhole slots incorporated into the bottom panel provide convenient wall or desk mounting options for the black plastic housing.

Features

790-Joule Surge Protection for Home or Office ElectronicsProtects your computer, printer, scanner, router, modem and other small home electronics against even the strongest surges and

Highlights

- 6 NEMA 5-15R outlets—one designed for a bulky transformer
- 790-joule surge protection rating
- Filters out threatening EMI/RFI line noise
- 15A resettable circuit breaker prevents dangerous overloads
- 6-ft. (1.83 m) AC power cord with NEMA 5-15P plug

Package Includes

- TLP606B Protect It! 6-Outlet
 Surge Protector, Black Housing
- Owner's manual



spikesRecommended for any desktop, network or home electronics application requiring AC line protectionFull normal mode (H-N) and common mode (N-G/H-G) line surge suppressionFilters out disruptive EMI/RFI line noise that can cause equipment damage or data lossExceeds IEEE 587 Category A and B surge suppression specifications

6 Outlets Accept Wide Range of Electronic Devices 6 NEMA 5-15R AC outlets accept most computers and peripheralsSpecial end outlet designed for bulky transformers without blocking other outlets Premium Safety FeaturesLighted on/off switch provides one-touch control over connected equipmentAutomatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is requiredDiagnostic LED confirms protection status at a glanceConforms to current UL 1449 3rd Edition safety standards

Fits Effortlessly Into Your Workstation6-ft. (1.83 m) AC power cord with NEMA 5-15P plug reaches nearby outletsKeyhole slots on bottom panel provide convenient wall or desk mounting optionsBlack plastic housing designed for long life

Backed by Tripp Lite's Ultimate Lifetime Insurance \$20,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

Specifications

| OVERVIEW | | |
|------------------------------------|---|--|
| UPC Code | 037332138293 | |
| INPUT | | |
| Nominal Input Voltage(s) Supported | 120V AC | |
| Recommended Electrical Service | 120V (110-125V) | |
| Input Cord Gauge Type | 14 gauge; SJT | |
| Voltage Compatibility (VAC) | 120 | |
| Maximum Surge Amps | 35500 | |
| Input Plug Type | NEMA 5-15P | |
| Input Cord Length (ft.) | 6 | |
| Right-Angle Plug | No | |
| Input Cord Length (m) | 1.83 | |
| Integrated Cord Clip | No | |
| OUTPUT | | |
| Frequency Compatibility | 50 / 60 Hz | |
| Output (Watts) | 1800 | |
| Output Receptacles | (6) 5-15R | |
| Circuit Breaker (amps) | 15 | |
| Overload Protection | 15A resettable illuminated combo switch / circuit breaker | |
| Transformer Accommodation | (2) Yes | |
| Outlet Orientation | Single row of 6 outlets | |
| Right-Angle Outlets | No | |



Γ

| USER INTERFACE, ALERTS & CONTROLS | | |
|---|--|--|
| Diagnostic LED(s) | Yes | |
| Switches | Combination AC circuit breaker and 2 position red illuminated on/off power switch | |
| Diagnostic LED Details | Built-in LED confirms suppressor "protection present" (green) status | |
| SURGE / NOISE SUPPRESSION | | |
| AC Suppression Joule Rating | 790 | |
| AC Suppression Response Time | < 1 ns | |
| Protection Modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression | |
| Clamping Voltage (RMS) | 150 | |
| UL1449 Let Through Rating | 400V | |
| EMI / RFI Filtering | Yes | |
| Automatic Shut-Off | Yes | |
| DATALINE SURGE SUPPRESSION | | |
| Telephone/DSL Protection | No | |
| Cable (Coax) Protection | No | |
| Network (Ethernet) Protection | No | |
| PHYSICAL | | |
| Antimicrobial Coating | No | |
| Color | Black | |
| Color (AC Line Cord) | Black | |
| Housing Color | Black | |
| Integrated Keyhole Mounting Slots | Yes | |
| Keyhole Slot Mounting Measurement (Center to Center) | Distance between slots = 101mm; Distance between slot height = 28mm | |
| Material of Construction | Plastic | |
| Outlets Measurement (Center to Center) | 28.5mm | |
| Receptacle Color | Black | |
| Shipping Dimensions (hwd / cm) | 31.75 x 4.06 x 12.70 | |
| Shipping Dimensions (hwd / in.) | 12.50 x 1.60 x 5.00 | |
| Shipping Weight (kg) | 0.54 | |
| Shipping Weight (lbs.) | 1.20 | |
| Unit Dimensions (hwd / cm) | 27.43 x 4.70 x 3.12 | |
| Unit Dimensions (hwd / in.) | 10.8 x 1.85 x 1.23 | |



| | 1 |
|---|---|
| Unit Weight (kg) | 0.46 |
| Unit Weight (Ibs.) | 1.01 |
| SPECIAL FEATURES | |
| Rotatable Outlets | No |
| STANDARDS & COMPLIANCE | |
| Canada | cUL |
| Additional International Approvals | RoHS |
| Approvals | Exceeds IEEE 587 category A&B specifications |
| UL1449 3rd Edition (AC Suppression) | UL1449 3rd EDITION |
| UL1363 (Power Tap) | UL1363 |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$20,000 Ultimate Lifetime Insurance |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies