


Prefabricated Gate Jumper Assembly – A238KC2S24LH



- Ideal for when nVent ERICO Cadweld connections cannot be made to aluminum pipe or thin-wall steel tube
- Jumper conductor is insulated
- Stainless steel hardware included
- Available in either left or right-hand orientation



Part Number	A238KC2S24LH
Material	Copper Stainless Steel 18-8 (EN 1.4305) Stainless Steel 304 (EN 1.4301)
Finish	Tinned
Orientation	Left Hand
Fixed Gate Diameter, Nominal	6"
Fixed Gate Diameter, Actual (Ø1)	6.63"
Post Frame Diameter, Nominal	1 1/2"
Post Frame Diameter, Actual (Ø2)	1.9"
Jumper Conductor Size	4/0 Stranded
Jumper Length	24"
Standard Packaging Quantity	1 pc
UPC	78285669484

"Fixed gate" refers to the pipe on the fence itself, while "post frame" refers to the post on the swinging door.
Left hand orientation shown in diagram.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.