Rebar Grounding Clamp, Parallel – EK16











- Universal use for rebar, rods or pipes ٠
- Lay-in feature cuts installation time •
- Bronze alloy construction with Stainless Steel 304 screws
- ٠ Approved for direct burial in earth and concrete





Part Number	ЕК16
Material	Bronze Stainless Steel 304 (EN 1.4301)
Connection Type	Parallel
Conductor Size	#10 Solid - #2 Solid 5.5 mm² Stranded - 25 mm² Stranded
Ground Rod Diameter, Actual (Ø)	0.5" – 1.0"
Water Pipe Size (Ø)	1/2" – 1"
Rebar Size, Metric	12 – 25 mm
Rebar Size, US	#4 - #8
Rebar Size, Canada	10M – 25M
Certifications	cULus
Standard Packaging Quantity	50 рс
UPC	78285657555
EAN-13	8711893041699

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



